






















2021-09-30		SPECYFIKACJA DO RYSUNKU NR:		K08					1 / 5	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	$\Phi$	$\Phi$	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		na 1 el.	na $\Sigma$ el.			
1	2	3	4	5	6	7	8	9	10	11
Ściana "D"	36		-	12	235.0	-	53	124.6	110.6	S= 422.9
	37		-	12	235.0	-	53	124.6	110.6	
	60	227.2 mb	-	12	227.2 mb	-	-	227.2	201.7	
Doświetle powyżej kanału	5		-	12	635.0	-	32	203.2	180.4	S= 437.6
	6		-	12	608.0	-	6	36.5	32.4	
	13		-	12	400.0	-	60	240.0	213.1	
	17		-	12	331.0	-	4	13.2	11.8	
Ściana "E"	76		-	12	172.0	-	25	43.0	38.2	S= 141.0
	77		-	12	172.0	-	25	43.0	38.2	
	79	72.8 mb	-	12	72.8 mb	-	-	72.8	64.6	
Otwór "O"	69		-	8	87.0	-	80	69.6	27.5	S= 48.4
	70		-	8	87.0	-	41	35.7	14.1	
	74	17.42 mb	-	8	17.4 mb	-	-	17.4	6.9	
Płyta "P1" szt. 4	26		-	12	286.0	12	48	137.3	121.9	S= 252.1
	55		-	12	135.0	26	104	140.4	124.6	
	72		-	8	43.8	8	32	14.0	5.5	
Płyta "P2" szt. 2	34		-	12	246.0	14	28	68.9	61.2	S= 122.9
	48		-	12	151.0	22	44	66.4	59.0	
	72		-	8	43.8	8	16	7.0	2.8	
Płyta "P3"	34		-	12	246.0	-	6	14.8	13.1	S= 52.3
	40		-	12	219.0	-	6	13.1	11.7	
	48		-	12	151.0	-	20	30.2	26.8	
	59		-	12	80.0	-	1	0.8	0.7	

2021-09-30		SPECYFIKACJA DO RYSUNKU NR:		K08					2 / 5	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	$\Phi$	$\Phi$	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		na 1 el.	na $\Sigma$ el.			
1	2	3	4	5	6	7	8	9	10	11
Płyta "P3"	72		-	8	43.8	-	8	3.5	1.4	S= 1.4
Płyta "P4" szt. 5	26		-	12	286.0	12	60	171.6	152.3	S= 309.3
	56		-	12	130.0	26	130	169.0	150.0	
	72		-	8	43.8	8	40	17.5	6.9	
Płyta "P5"	75		-	12	241.0	-	58	139.8	124.1	S= 204.8
	78		-	12	154.0	-	58	89.3	79.3	
	80		-	8	43.8	-	8	3.5	1.4	
Płyta fundamentowa	1		-	12	819.0	-	29	237.5	210.9	S= 1295.2
	4		-	12	719.0	-	29	208.5	185.1	
	8		-	12	554.0	-	29	160.7	142.6	
	10		-	12	450.0	-	29	130.5	115.9	
	11		-	12	445.9	-	10	44.6	39.6	
	13		-	12	400.0	-	18	72.0	63.9	
	17		-	12	331.0	-	2	6.6	5.9	
	21		-	12	322.0	-	11	35.4	31.4	
	25		-	12	299.0	-	28	83.7	74.3	
	26		-	12	286.0	-	140	400.4	355.5	
	33		-	12	255.0	-	10	25.5	22.6	
	34		-	12	246.0	-	4	9.8	8.7	
	39		-	12	220.0	-	8	17.6	15.6	
	43		-	12	186.0	-	14	26.0	23.1	























2021-09-30

SPECYFIKACJA DO RYSUNKU NR:

K08

3 / 5

ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	$\Phi$	$\Phi$	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		na 1 el.	na $\Sigma$ el.			
1	2	3	4	5	6	7	8	9	10	11
Płyta fundamentowa	61		-	10	1200.0	-	28	336.0	207.2	S= 323.7
	63		-	10	576.0	-	28	161.3	99.4	
	66		-	10	99.0	-	28	27.7	17.1	
Płyta górna	4		-	12	719.0	-	29	208.5	185.1	S= 1149.9
	10		-	12	450.0	-	62	279.0	247.7	
	15		-	12	360.0	-	4	14.4	12.8	
	30		-	12	260.0	-	4	10.4	9.2	
	35		-	12	242.0	-	29	70.2	62.3	
	44		-	12	179.0	-	116	207.6	184.3	
	45		-	12	177.0	-	58	102.7	91.1	
	47		-	12	160.0	-	29	46.4	41.2	
	64		-	10	574.0	-	58	332.9	205.3	
	65		-	10	310.0	-	58	179.8	110.9	
Ściana "S"	41		-	12	206.0	-	170	350.2	310.9	S= 1151.0
	42		-	12	206.0	-	170	350.2	310.9	
	60		-	12	596.0 mb	-	-	596.0	529.1	
Ściana 1	2		-	12	779.0	-	58	451.8	401.1	S= 675.6
	12		-	12	402.0	-	14	56.3	50.0	
	16		-	12	335.0	-	58	194.3	172.5	
	24		-	12	300.0	-	1	3.0	2.7	
	28		-	12	266.5	-	8	21.3	18.9	
	29		-	12	280.0	-	8	22.4	19.9	
	46		-	12	169.0	-	7	11.8	10.5	














ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP	l	na 1 el.	na Σ el.	L	wg Φ	Σ
1	2	3	4	5	6	7	8	9	10	11
Ściana 1	50		-	12	150.0	-	58	87.0	77.2	Σ= 104.8
	52		-	12	141.0	-	22	31.0	27.5	
Ściana 2	9		-	12	512.0	-	20	102.4	90.9	Σ= 436.9
	16		-	12	335.0	-	28	93.8	83.3	
	18		-	12	330.0	-	2	6.6	5.9	
	19		-	12	323.0	-	12	38.8	34.4	
	20		-	12	323.0	-	12	38.8	34.4	
	23		-	12	315.0	-	16	50.4	44.7	
	27		-	12	272.0	-	12	32.6	29.0	
	38		-	12	228.0	-	12	27.4	24.3	
	49		-	12	151.0	-	20	30.2	26.8	
	50		-	12	150.0	-	28	42.0	37.3	
	51		-	12	149.0	-	10	14.9	13.2	
	57		-	12	107.0	-	12	12.8	11.4	
	71		-	8	80.0	-	4	3.2	1.3	
Ściana 3	3		-	12	778.0	-	58	451.2	400.6	Σ= 1026.8
	7		-	12	572.0	-	58	331.8	294.5	
	14		-	12	398.0	-	16	63.7	56.5	
	16		-	12	335.0	-	58	194.3	172.5	
	19		-	12	323.0	-	12	38.8	34.4	
	20		-	12	323.0	-	12	38.8	34.4	
	22		-	12	317.5	-	12	38.1	33.8	

2021-09-30

SPECYFIKACJA DO RYSUNKU NR:

K08

5 / 5

ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	$\Phi$	$\Phi$	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		na 1 el.	na $\Sigma$ el.			
1	2	3	4	5	6	7	8	9	10	11
Ściana 3	31		-	12	259.5	-	6	15.6	13.8	Σ= 226.9
	32		-	12	259.5	-	6	15.6	13.8	
	50		-	12	150.0	-	58	87.0	77.2	
	54		-	12	136.0	-	58	78.9	70.0	
	58		-	12	101.0	-	58	58.6	52.0	
"Ściana 4"	9		-	12	512.0	-	58	297.0	263.6	Σ= 513.4
	16		-	12	335.0	-	58	194.3	172.5	
	50		-	12	150.0	-	58	87.0	77.2	
Wspornik "V"	53		-	12	138.0	-	74	102.1	90.7	Σ= 235.7
	67		-	8	130.0	-	74	96.2	38.0	
	68		-	8	88.0	-	74	65.1	25.7	
	73		-	8	64.0	-	222	142.1	56.1	
	74		-	8	64.2 mb	-	-	64.2	25.3	