




























ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		na 1 el.	na Σ el.			
1	2	3	4	5	6	7	8	9	10	11
Schody "A"	18		-	8	135.5	-	9	12.2	4.8	$\Sigma = 25.3$
	19		-	8	86.3	-	9	7.8	3.1	
	20		-	8	83.7	-	9	7.5	3.0	
	21		-	8	70.0	-	9	6.3	2.5	
	23		-	8	30.3 mb	-	-	30.3	11.9	
Belka "B"	2		-	12	475.0	-	9	42.8	38.0	$\Sigma = 218.6$
	4		-	12	420.0	-	3	12.6	11.2	
	5		-	12	396.0	-	16	63.4	56.3	
	6		-	12	350.0	-	2	7.0	6.2	
	7		-	12	285.0	-	9	25.7	22.8	
	9		-	12	230.0	-	9	20.7	18.4	
	10		-	12	190.0	-	9	17.1	15.2	
	11		-	12	171.0	-	9	15.4	13.7	
	13		-	12	45.0	-	12	5.4	4.8	
	16		-	10	85.0	-	6	5.1	3.1	
	17		-	8	145.0	-	43	62.4	24.6	
	24		6	-	105.0	-	19	20.0	4.4	
Płyta	1		-	12	500.0	-	9	45.0	40.0	$\Sigma = 128.6$
	3		-	12	425.0	-	9	38.3	34.0	
	8		-	12	283.0	-	9	25.5	22.6	
	12		-	12	119.0	-	9	10.7	9.5	
	16		-	10	85.0	-	6	5.1	3.1	
	17		-	8	145.0	-	34	49.3	19.5	

2021-09-30		SPECYFIKACJA DO RYSUNKU NR:			K5			2 / 2		
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			St3SX	B500SP		l	na 1 el.	na Σ el.	L	wg Φ
1	2	3	4	5	6	7	8	9	10	11
D	1		-	12	54.0	-	3	1.6	1.4	S= 1.4
Płyta	15		-	10	565.0	-	78	440.7	271.7	S= 271.7
Wieniec "W"	14		-	12	29.0 mb	-	-	29.0	25.7	S= 35.1
	22		-	8	70.0	-	34	23.8	9.4	